



AESSEAL PACKING STYLE 326

Synthetic Staple fiber with special Graphite Impregnation and Run In Lubricant

Characteristics

- Volume stable, pressure stable
- High Cross section density due to special impregnation
- Excellent Value for money
- Graphitized all-round packing with Emergency run Capabilities
- Good wear resistance against abrasive and crystallizing products
- Recommended shaft surface hardness: HRC 45

Operating range

			
p [bar]	20	250	150
v [m/s]	20	2	
t °C	-50 ... +180		
pH	5 - 12		
g/cm ³	1.23		

Practical useful application data:
max. temperature: +140 °C

Main application

- Centrifugal pumps
- Valves
- Mixer
- Kneader
- Agitators

Suitable for

- Chemical industry
- Pulp and paper industry
- Waste water technology
- Community facilities



Form of delivery

This packing can be manufactured from 4 to 40 mm square as well as in intermediate, inch sizes and special measurements.

- 04 - 09 mm on 1 kg spool
- 10 - 15 mm on 2,5 kg spool
- 16 - 25 mm on 5 kg spool

Special length, pre-cut or die formed rings on request.

1 kg of packing of the following cross-sections is equivalent to displayed meter lengths:

Size mm	Meter	Size mm	Meter
4	50.8	13 [1/2"]	5.0
5 [3/16"]	32.5	14 [9/16"]	4.1
6	22.6	15	3.6
6.4 [1/4"]	20.2	16 [5/8"]	3.2
8 [5/16"]	12.7	18	2.5
9.5 [3/8"]	9.0	19 [3/4"]	2.3
10	8.1	20	2.0
11 [7/16"]	6.6	22 [7/8"]	1.7
12	5.6	25 [1"]	1.3

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.