ENVIRONMENTAL TECHNOLOGY



AESSEAL PACKING STYLE 830

Cotton with tallow/grease and Run In Lubricant

Characteristics

- Universal packing for the lower temperature range
- Excellent value for money
- Shaft protecting, resistant to rotting
- Recommended shaft surface hardness: HRC 45
- Excellent in products containing solids

Operating range

p [bar]	20	50	50
v [m/s]	10	2	
t °C	-20 ... +100		
pH	5 - 13		
g/cm³	1.45		

Main application

- Centrifugal pumps
- Piston pumps
- Gate valves
- Fittings
- Agitators
- Refiner
- Hydrants
- Stern Tube

Suitable for

- Universal use in lower temperature range
- Pulp and paper industry
- Sewage plants
- Marine industries





Form of delivery

This packing can be manufactured from 8 to 30 mm square as well as in intermediate, inch sizes and special measurements.
8 - 25 mm on 5 kg spool

1 kg of packing of the following cross-sections is equivalent to displayed meter lengths:

Size mm	Meter	Size mm	Meter
8 [5/16"]	10.8	18	2.1
9.5 [3/8"]	7.6	19 [3/4"]	1.9
10	6.9	20	1.7
11 [7/16"]	5.6	22 [7/8"]	1.4
12	4.8	25 [1"]	1.1
13 [1/2"]	4.3		
14 [9/16"]	3.5		
15	3.1		
16 [5/8"]	2.7		

AESSEAL © 2021 | 08/21 | EN-03 | LN-830

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.
Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.
Please note that the technical values cannot be used all at the same time in their maximum values.

AESSEAL plc Packing Division Europe
Rudolf-Diesel-Ring 26a . 82054 Sauerlach . Germany

Telephone: +49 8104 6640-21 . Telefax: +49 8104 6640-44
packing.euro@aesseal.com . www.aesseal.com