






ENVIROSTAR 200BR

Pre-compressed Packing Set of specially impregnated PTFE fiber packing

Characteristics

Ring set made of pure PTFE packing fulfills with a tested leakage of 6.3×10^{-6} mbar · l/(s·m) the leakage criteria according to VDI 2440 +390 °F with a maximum allowable leakagerate of 1×10^{-4} mbar l/(sm) at 580 psi.

Operating range

			
p [psi]	360	3630	7250
v [fpm]	390	0	-
t °F	-330 ... +540		
pH	0 - 14		

Main application

- Valves
- Flaps
- Gate valves
- Fittings

Suitable for

- Power plant technology
- Chemical industry
- Petrochemical plants

Approvals

- TA Luft / VDI 2440 Certificate



AESSEAL © 2021 | 01/21 | EN-03 | LW - ENVIROSTAR 200BR

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. Please note that the technical values cannot be used all at the same time in their maximum values.

AESSEAL plc Packing Division Europe
Rudolf-Diesel-Ring 26a . 82054 Sauerlach . Germany

Telephone: +49 8104 6640-21 . Telefax: +49 8104 6640-44
packing.euro@aes seal.com . www.aes seal.com

www.aes seal.com