

# ISOS TM Inflatable Shut Off Seal



- For use in conjunction with radially divided seals
- Allows easier and quicker replacement of a mechanical seal without having to drain equipment
- Allows replacement of seal when pump shut off valves are faulty
- Eliminates the need for pump shut off valves when replacing seal
- No re-priming of pumps needed after seal replacement
- Once inflated by a suitable and continuous supply it forms a pressurized seal for zero product leakage

www.aesseal.com

## ISOS<sup>™</sup> - inflatable shut off seal

### Most engineers will relate to the problems encountered when installing or removing a radially divided mechanical seal from rotating equipment.

However, the biggest single problem is that the whole system has to be drained or isolated so that liquids do not pour out when the seal is

removed. This can sometimes take hours or even days depending on the application - all lost production time.

## Introducing the AESSEAL<sup>®</sup> ISOS<sup>™</sup> - the Inflatable Shut Off Seal, which solves this major problem.

The ISOS<sup>™</sup>, which is fitted between the pump and radially divided seal, forms a separate seal when required, allowing the quick and easy removal of the mechanical seal.







#### ISOS<sup>™</sup> and RDS<sup>™</sup> shown together

The ISOS<sup>™</sup> works around the principle of surrounding the shaft with an inflatable elastomeric bladder. Under normal operating conditions, when the mechanical seal is working, the bladder remains unpressurized.

When the mechanical seal fails or needs removing, the bladder can be inflated thereby mechanically sealing the shaft. The seal can then be easily removed without draining or isolating the equipment.

#### Note - can be pressurized by air or water.



#### ISOS<sup>™</sup> - Inventoried Bladder Sizes

Metric (mm)		
	63	
	70	
	75	
	90	
	100	
	127	
	245	

All metal components are designed to suit the application and made to order only.

ltem	Description	Material
1	Main Housing	316L Stainless Steel
2	Housing O Ring	FKM / EPR / FFKM / TFE/P
3	Inflatable Bladder	EPR
4	Inner Ring	316L Stainless Steel
5	Bladder O Ring	FKM / EPR / FFKM / TFE/P
6	Cover Plate	316L Stainless Steel
7	Caphead Bolt	Stainless Steel



# **ISOS<sup>™</sup>** - operation using the AESSEAL<sup>®</sup> RDS<sup>™</sup> Mechanical Seal





The pump is stopped, the Bladder is inflated and then seals onto the shaft. The radially divided seal can then be drained of fluid by its flush port.



Bladder is still inflated and a new seal is installed.



Seal in operation. The bladder is uninflated.



Whilst the bladder is inflated the seal is replaced.



Bladder is deflated, the seal is primed and set to run again.

# **RDS<sup>™</sup> - Radially Divided Seal**



The AESSEAL<sup>®</sup> RDS<sup>™</sup> (Radially Divided Seal) is an ideal seal to be used in conjunction with the ISOS<sup>™</sup> due to its unique separation technology.

The RDS<sup>™</sup> mechanical seal has been designed to be the fastest two-part seal to install in the market place and includes the following features:

- Minimum parts to assemble
- Patented assembled spring retainer
- External, visible indicator of correct installation
- Balanced stationary design with large internal clearances
- Unique patented 'O' Ring design
- Sizes available from 2.500" to 12.000" (63mm to 300mm)

It represents a significant advancement in separation technology and bridges the gap between pump packing and conventional mechanical seals.

Significant product development and dynamic testing were aimed at ensuring that the operating performance of the RDS<sup>™</sup> seal would be predictable.

This brochure is available by contacting the Marketing department at **marketing@aesseal.com** or can be downloaded by visiting our website at **www.aesseal.com** 

🚯 This brochure is fully recyclable. When laminated, a sustainable, biodegradable and recyclable lamination is used. 🚯

For further information and safe operating limits contact our technical specialists at the locations below.



UK Sales & Technical advice: AESSEAL plc Mill Close Bradmarsh Business Park Rotherham, S60 1BZ, UK

Tel: +44 (0) 1709 369966 E-mail: enquiries@aesseal.info www.aesseal.com

#### AESSEAL plc is certified to: ISO 9001, ISO 14001, ISO/IEC 20000, ISO/IEC 27001,





Tel: +1 865 531 0192 E-mail: inquiries@aesseal.us

USA

Important: Since the conditions and methods of use of this product are beyond our control, AESSEAL plc expressly disclaims any and all liability resulting or arising from any use of this product or reliance on any information contained in this document - AESSEAL plc standard conditions of sale apply. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. AESSEAL® is a Registered Trademark of AES Engineering Ltd, AESSEAL plc recognizes all trademarks and trademark names as the property of their owners. LIT-UK/US-L-ISOS-07PDF Copyright © 2025 AESSEAL plc 02/2025