# **FLOWTRUE**<sup>TM</sup>

# Installation Operations & Maintenance Instructions





# AESSEAL (MCK) Ltd.

139A Hillsborough Old Road Lisburn, N. Ireland, BT27 5QE

Tel: +44 (0) 28 9266 9966 Email: MCK@aesseal.co.uk www.aesseal.com



## **Health and Safety**

- Before attempting work on any process equipment, ensure that all permit requirements are satisfied and all necessary process, electrical and mechanical isolations are in place.
- The system should be installed by comptent engineering personnel.
- Do not over-pressurise the FLOWTRUE<sup>™</sup> beyond the maximum design pressure. If there is any possibility of over-pressurisation the system must be fitted with a suitable protection device contact AESSEAL for advice.
- Do not exceed the operating limits of the FLOWTRUE™.
- The FLOWTRUE™ supply connections may get hot in operation with risk of burn injury.
- Ensure the FLOWTRUE™ is completely leak free before full operation.
- This system has been designed for use only as a flow meter for mechanical seals using water



Once the barrier fluid and system have reached the end of its life, it should be disposed of in accordance with local regulations and with due regard to the environment.

# For further information please contact AESSEAL®



Installing & Commissioning

## Installation & Commissioning

- 1) New or renewed plant water lines need to be flushed correctly to prevent harmful particles from passing through the FLOWTRUE<sup>™</sup> valve and seal. Ensure that the plant water supply is closed for stages 2 5
- 2) Install the FLOWTRUE<sup>™</sup> in a suitable location which is free from vibration and in close proximity to the pump. The meter should be mounted so that it is easy to read and maintain.
- 3) Connect the hoses from the plant water supply to the FLOWTRUE™ (I) and from the FLOWTRUE™ connection (J) to the mechanical seal.
- 4) If installing Model FTPB XX YYY for use with a double mechanical seal (Figure 3), there is both a backpressure valve (M) and a pressure gauge (O). The hose from the mechanical seal leading back to the FLOWTRUE<sup>™</sup> is connected to return connection (K).
- 5) Ensuring that the flow valve (H) is closed, set the red target flow indicator (C) to the desired flow rate using the 2.5mm allen key (G).
- 6) Switch on the plant water supply. Open the flow valve (H) until the white left hand ring (D) is in line with the red flow indicator (C).
- 7) If installing Model FTPB XX YYY for use with a double mechanical seal (**Figure 3**), adjust the red target pressure indicator (P) to the pressure you desire. Use allen key (G) in the back pressure control valve adjustment point (N) until the desired pressure is reached.

#### Alarm Option (if selected)

- Remove the alarm label from the top of the FLOWTRUE device and attach the alarm using the screws supplied.
- Attach the alarm cables to a suitable control panel.
- Using the FLOWTRUE allen key (G), adjust the flow control valve (H) until the flow indicator ring (D) is at the minimum flow rate acceptable for the application. This will be known as the **flow alarm valve**.
- Loosen the screws and move the alarm to the far left of the alarm slot. Then, move the alarm to the right until the light on the alarm comes on.
- When the light comes on, tighten the alarm in position using the screws supplied.
- Using the FLOWTRUE allen key, adjust the target flow indicator (C) (red marker) to the desired flow for the application.
- Using the FLOWTRUE allen key (G), adjust the flow control valve (H) until the flow indicator ring (D) is in line with the target flow indicator (C) (red marker).
- The alarm light will remain on until the flow drops below the **flow alarm valve.** This will trigger the selected alarm device on the control panel.

#### **Cleaning Operation**

- 1) Un-screw cleaning button (A) by rotating it anti-clockwise.
- 2) Pull the cleaning button out of the main body. Push the button back and forth until the cleaning ring (E) clears the flow tube.
- 3) Push the cleaning button (A) back into the main body and tighten by rotating it clockwise until hand tight.



#### **Operating Limits:**

Polyacetal (standard body material, white in colour)

- Maximum Pressure = 25 bar / 360 psi
- Maximum Temperature = 80°C / 176°F

#### Polyethylene (chemical environments body material, yellow in colour)

- Maximum Pressure = 10 bar / 145 psi
- Maximum Temperature = 60°C / 140°F

For 316 Systems, when used with a water based barrier/buffer the Chloride content should not exceed 250ppm.